

GAM Run 08-01

by **Kan Tu, Ph.D., P.G.**

Texas Water Development Board
Groundwater Availability Modeling Section
(512) 475-2132
March 10, 2008

EXECUTIVE SUMMARY:

Texas State Water Code, Section 36.1071, Subsection (h), states that, in developing its groundwater management plan, a groundwater conservation district shall use groundwater availability modeling information provided by the executive administrator in conjunction with any available site-specific information provided by the district and acceptable to the executive administrator. Information derived from groundwater availability models that shall be included in groundwater management plans include:

- (1) the annual amount of recharge from precipitation, if any, to the groundwater resources within the district;
- (2) for each aquifer within the district the annual volume of water that discharges from the aquifer to springs and any surface water bodies, including lakes, streams, and rivers; and
- (3) the annual volume of flow into and out of the district within each aquifer and between aquifers in the district.

The purpose of this groundwater availability model run is to provide information to the Bee Groundwater Conservation District needed for its groundwater management plan. The groundwater management plan for the Bee Groundwater Conservation District is due for approval by the executive administrator of the TWDB before October 2, 2008.

This report discusses the method, assumptions, and results from model runs using the groundwater availability models for the central part of the Gulf Coast Aquifer and the southern part of the Carrizo-Wilcox, Queen City, and Sparta aquifers. Table 3 summarizes the groundwater availability model data required by statute for the Bee Groundwater Conservation Districts groundwater management plan.

METHODS:

We ran the groundwater availability models for the central part of the Gulf Coast Aquifer and the southern part of the Carrizo-Wilcox, Queen City, and Sparta aquifers and (1) extracted water budgets for each year of the 1980 or 1981 through 1999 period and (2) averaged the annual water budget values for recharge, surface water inflow, surface water outflow, inflow to the district, outflow from the district, net inter-aquifer flow (upper) and net inter-aquifer flow (lower) for the

portions of the Gulf Coast Aquifer and the Carrizo-Wilcox, Queen City and Sparta aquifers located within the district.

PARAMETERS AND ASSUMPTIONS:

Groundwater availability model for the central part of the Gulf Coast Aquifer

- We used Version 1.01 of the groundwater availability model for the central part of the Gulf Coast Aquifer. See Chowdhury and others (2004) and Waterstone and others (2003) for assumptions and limitations of the groundwater availability model for the central part of the Gulf Coast Aquifer.
- The model simulates groundwater flow through four hydrostratigraphic layers. From top to bottom, these layers are: the Chicot Aquifer, Evangeline Aquifer, Burkeville Confining System, and the Jasper Aquifer.
- The mean absolute error (a measure of the difference between simulated and actual water levels during model calibration) in the entire model for 1999 is 26 feet, which is 4.6 percent of the hydraulic head drop across the model area (Chowdhury and others, 2004).
- The transient portion of the model has a total of 85 stress periods. Of these, monthly stress periods were assigned for 1987 through 1989 and 1996 through 1998. Monthly stress periods were assigned to better simulate possible effects of drought on the groundwater flow system. The remainders of the stress periods represent annual stress periods.

Groundwater availability model for the southern part of the Carrizo-Wilcox, Queen City, and Sparta aquifers

- We used Version 2.01 of the groundwater availability model for the southern part of the Carrizo-Wilcox, Queen City and Sparta aquifers. See Deeds and others (2003) and Kelley and others (2004) for assumptions and limitations of the groundwater availability model for the southern part of the Carrizo-Wilcox, Queen City, and Sparta aquifers.
- The groundwater availability model includes eight layers, representing:
 1. the Sparta Aquifer (Layer 1),
 2. the Weches Confining Unit (Layer 2),
 3. the Queen City Aquifer (Layer 3),
 4. the Reklaw Confining Unit (Layer 4),
 5. the Carrizo Aquifer (Layer 5),
 6. the Upper Wilcox Aquifer (Calvert Bluff Formation—Layer 6),
 7. the Middle Wilcox Aquifer (Simsboro Formation—Layer 7), and
 8. the Lower Wilcox Aquifer (Hooper Formation—Layer 8).

- The root mean squared error (a measure of the difference between simulated and actual water levels during model calibration) in the groundwater availability model is 23 feet for the Sparta Aquifer, 18 feet for the Queen City Aquifer, and 33 feet for the Carrizo Aquifer for the calibration period (1980 to 1989) and 19, 22, and 48 feet for the same aquifers, respectively, in the verification period (1990 to 1999) (Kelley others, 2004). These root mean squared errors are between seven and ten percent of the range of measured water levels (Kelley others, 2004).

We used Groundwater Vistas Version 5 (Environmental Simulations, Inc. 2007) as the interface to process model output results.

RESULTS:

A groundwater budget summarizes the water entering and leaving the aquifer according to the groundwater availability model. The groundwater budget for the annual average values for the Gulf Coast Aquifer in the district (1981 to 1999) is shown in Table 1. Table 2 shows the groundwater budget for the Carrizo-Wilcox, Queen City, and Sparta aquifers (1980 to 1999) in the district. The components of the modified budgets shown in Tables 1 and 2 include:

- Surface water inflow and outflow—This is the total surface water entering the aquifer (inflow) through streams or reservoirs and the total surface water exiting the aquifer (outflow) to streams, reservoirs, drains (springs), and through evapotranspiration (return of moisture to the air through both evaporation from the soil and transpiration or loss of water vapor by plants).
- Lateral flow into and out of district—This component describes lateral flow within the aquifer between the district and adjacent counties.
- Net inter-aquifer flow—This describes the vertical flow, or leakage, between aquifers or confining units. This flow is controlled by the relative water levels in each aquifer or confining unit and aquifer properties of each aquifer or confining unit that define the amount of leakage that occurs. “Inflow” to an aquifer from an overlying or underlying aquifer will always equal the “Outflow” from the other aquifer.
- Precipitation recharge—This is the areally distributed recharge sourced from precipitation falling on the outcrop areas of the aquifers (where the aquifer is exposed at land surface) within the district.

The information needed for the district’s management plan is summarized in Table 3.

It is important to note that sub-regional water budgets for individual counties, such as Bee County, are not exact. This is due to the one-mile spacing of the model grid and because we assumed each model cell is assigned to a single county. The water budgets for an individual cell containing a county boundary are assigned to either one county or the other and therefore very minor variations in the county-wide budgets may be observed.

As depicted by Kalaswad and Arroyo (2006) and Kelley and others (2004), groundwater in the Gulf Coast Aquifer and the Carrizo-Wilcox, Queen City, and Sparta aquifers ranges from fresh to saline. The reported values in this report for flow terms include fresh (less than 1,000 milligrams per liter total dissolved solids), brackish (1,000 to 10,000 milligrams per liter total dissolved solids), and saline (greater than 10,000 milligrams per liter total dissolved solids) groundwater.

REFERENCES:

- Chowdhury, A.H., Wade, S.W., Mace, R.E., and Ridgeway, C., 2004, Groundwater availability model of the central Gulf Coast Aquifer system—Numerical simulations through 1999: Unpublished Texas Water Development Board report, 114 p. http://www.twdb.state.tx.us/gam/glfc_c/glfc_c_TWDB_SummaryReport.pdf
- Deeds, N., Kelley, V.A., Fryar, D., Jones, T., Whallon, A.J., and Dean, K.E., 2003, Groundwater availability model for the Southern Carrizo-Wilcox Aquifer: Contract report to the Texas Water Development Board, 452 p.
- Environmental Simulations, Inc. 2007, Guide to Using Groundwater Vistas Version 5, 381 p.
- Kelley, V.A., Deeds, N.E., Fryar, D.G., and Nicot, J.P., 2004, Groundwater availability models for the Queen City and Sparta aquifers: Contract report to the Texas Water Development Board, 867 p.
- Kalaswad, S., and Arroyo, J., 2006, Status report on brackish groundwater and desalination in the Gulf Coast Aquifer of Texas *in* Mace, R.E., Davison, S.C., Angle, E.S., and Mullican, III, W.F., eds., Aquifers of the Gulf Coast of Texas: Texas Water Development Board Report 365, p. 231–240.
- Waterstone Environmental Hydrology and Engineering Inc. and Parsons, 2003, Groundwater availability of the Central Gulf Coast Aquifer: Numerical Simulations to 2050, Central Gulf Coast, Texas Contract report to the Texas Water Development Board, 157 p.

Table 1: Selected flow terms for each aquifer layer, into and out of the Bee Groundwater Conservation District, averaged for the years 1981 to 1999 from the groundwater availability model of the central part of the Gulf Coast Aquifer. Flows are reported in acre-feet per year. Note: a negative sign refers to flow out of the aquifer in the district. A positive sign refers to flow into the aquifer in the district. All numbers are rounded to the nearest 1 acre-foot. Flows include fresh, brackish, and saline waters.

Aquifer	Surface water inflow	Surface water outflow	Lateral inflow into district	Lateral outflow from district	Net inter-aquifer flow (upper)	Net inter-aquifer flow (lower)
Chicot (Layer 1)	4,490	-10,917	641	-8,692	0	-2,714
Evangeline (Layer 2)	2,224	-3,617	2,327	-6,794	2,714	-286
Burkeville (Layer 3)	41	0	36	-105	286	-628
Jasper (Layer 4)	16	-186	487	-816	628	0


Table 2: Selected flow terms for each aquifer layer, into and out of the Bee Groundwater Conservation District, averaged for the years 1980 to 1999 from the groundwater availability model of the southern part of the Carrizo-Wilcox, Queen City, and Sparta aquifers. Flows are reported in acre-feet per year. Note: a negative sign refers to flow out of the aquifer in the district. A positive sign refers to flow into the aquifer in the district. All numbers are rounded to the nearest 1 acre-foot. Flows include fresh, brackish, to saline waters.

Aquifer	Surface water inflow	Surface water outflow	Lateral inflow into district	Lateral outflow from district	Net inter-aquifer flow (upper)	Net inter-aquifer flow (lower)
Sparta (Layer 1)	0	0	2	-1	0	3
Weches (Layer 2)	0	0	20	-30	-3	21
Queen City (Layer 3)	0	0	2	-1	-21	34
Reklaw (Layer 4)	0	0	29	-26	-34	20
Carrizo (Layer 5)	0	0	163	-174	-20	8
Wilcox (Layer 6)	0	0	12	-8	-8	-1
Wilcox (Layer 7)	0	0	34	-12	1	3
Wilcox (Layer 8)	0	0	230	-150	-3	0

Table 3: Summarized information needed for the Bee Groundwater Conservation District's groundwater management plan. All values are reported in acre-feet per year. All numbers are rounded to the nearest 1 acre-foot.

Management plan requirement	Aquifer or confining unit	Results
Estimated annual amount of recharge from precipitation to the district	Chicot	16,737
	Evangeline	4,417
	Burkeville	1
	Jasper	22
	Sparta	0
	Weches	0
	Queen City	0
	Reklaw	0
	Carrizo	0
	Wilcox(upper)	0
	Wilcox(middle)	0
	Wilcox(lower)	0
Estimated annual volume of water that discharges from the aquifer to springs and any surface water body including lakes, streams, and rivers	Chicot	-10,917
	Evangeline	-3,617
	Burkeville	0
	Jasper	-186
	Sparta	0
	Weches	0
	Queen City	0
	Reklaw	0
	Carrizo	0
	Wilcox(upper)	0
	Wilcox(middle)	0
	Wilcox(lower)	0
Estimated annual volume of flow into the district within each aquifer in the district	Chicot	641
	Evangeline	2,327
	Burkeville	36
	Jasper	487
	Sparta	2
	Weches	20
	Queen City	2
	Reklaw	29
	Carrizo	163
	Wilcox(upper)	12
	Wilcox(middle)	34
	Wilcox(lower)	230

Management plan requirement	Aquifer or confining unit	Results
Estimated annual volume of flow out of the district within each aquifer in the district	Chicot	-8,692
	Evangeline	-6,794
	Burkeville	-105
	Jasper	-816
	Sparta	-1
	Weches	-30
	Queen City	-1
	Reklaw	-26
	Carrizo	-174
	Wilcox(upper)	-8
	Wilcox(middle)	-12
	Wilcox(lower)	-150
Estimated net annual volume of flow between each aquifer in the district	Chicot into Evangeline	2,714
	Evangeline into Burkeville	286
	Burkeville into Jasper	628
	Sparta into Weches	3
	Weches into Queen City	21
	Queen City into Rekalw	34
	Reklaw into Carrizo	20
	Carrizo into Wilcox (upper)	8
	Wilcox middle into upper	1
	Wilcox middle into lower	3



The seal appearing on this document was authorized by Kan Tu,

P.G., on March 10, 2008.